INDICATOR 5200 Weight indicator with extended scale functions

BENEFITS

- 5" full color Touch screen indicator with 25 mm high digits
- Extremely user friendly due to intuitive menu, only active keys are visible
- Integrated data connectivity as option available
- Counting functionality



Top quality Advanced functions











INDICATOR 5200

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- ID-code entry for max. 4 ID-codes with 10 preset codes (each max. 14 characters alpha-numeric)
- 10 totalizing registers
- Piece counting by entry or calculation of the piece weight
- Internal clock for date and time
- In board: RS232 port connection for printer

USB output for data transfer (with USB Stick) Free COM1 for WiFi, Bluetooth or RS232

Free COM2 for WiFi or RS232

Bluetooth 4.0 for RAVAS WeightsApp only

- The USB output can be used to connect a 1-D bar-code reader
- Load-bar in % to Q-max
- Error messages in display incl. logging

STANDARD SPECIFICATIONS

Display full-color 5" touch display with 25 mm

high digits digital

Segments high resolution touch display

0,1, 0,2, 0,5, 1, 2, 5, 10, 20 or 50 kg Graduation (see specifications sheet of the

weighing system)

Housing polymer (ABS) **Bracket** RAM bracket

Colour dark grey with red border

Protection class IP65 / NEMA 4

Power supply 12V (230V for stationary applications)

Power consumption 160 mA (without options)

Dimensions $L \times B \times H = 85 \times 165 \times 115 \text{ mm (excl.}$

bracket)





- Thermal or matrix printer
- WiFi and/or Bluetooth 2.0, RS232 option board for COM1 and COM2
- Ticket label printer
- Relay setpoint switch, for automatic dosing
- Analogue output -20 mA
- Legal for trade

- Multirange graduation (see specification sheet of the weighing system)
- RDC, RAVAS Data Collector Software
- RIS, RAVAS Integration Software

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands T: +31 418 515220 E: salesoffice@ravas.com WWW.RAVAS.COM

