

INDICATOR 2100

Weight indicator with basic scale functions

BENEFITS

- Developed for mobile use
- Compact, robust and shock proof
- Bluetooth data transfer
- Integrated voltage converter
- Dust and watertight



Top quality
Connects to WMS



RAVAS

INDICATOR 2100

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare
- Tare entry by cursor function
- Totaling with sequence number
- Error messages in display
- Printer power supply via indicator
- Automatic shut-off function defined by parameter settings
- Low battery indication

STANDARD SPECIFICATIONS

- Display: digital
- Segments: LCD, digit height 18 mm
- Graduation: 0.1, 0.2, 0.5, 1, 2, 5, 10, 20 or 50 kg (see specifications of weighing system)
- Housing: plastic (ABS)
- Bracket: steel
- Colour: red (RAL 3000)
- Protection class: IP65 / NEMA 4
- Power supply: 12V (230V for stationary applications)
- Dimensions: excl. bracket: 60 x 77 x 182 mm

OPTIONAL*

- Printer output to thermal or matrix printer
- Bluetooth or WLAN output
- RS232 output for cable connection to truck terminal
- Multirange graduation (see specifications weighing system)
- Explosion proof version (EXi)

RAVAS Europe B.V.

Toepadweg 7, 5301 KA Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

