

INDICATOR 5200

Weight indicator with extended scale functions

BENEFITS

- 5" full color Touch screen indicator with 25 mm high digits
- Extremely user friendly due to intuitive menu, only active keys are visible
- Integrated data connectivity as option available
- Counting functionality



Top quality

Advanced functions



FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- ID-code entry for max. 4 ID-codes with 10 preset codes (each max. 14 characters alpha-numeric)
- 10 totalizing registers
- Piece counting by entry or calculation of the piece weight
- Internal clock for date and time
- In board:
 - RS232 port connection for printer
 - USB output for data transfer (with USB Stick)
 - Free COM1 for WiFi, Bluetooth or RS232
 - Free COM2 for WiFi or RS232
 - Bluetooth 4.0 for RAVAS WeightsApp only
- The USB output can be used to connect a 1-D bar-code reader
- Load-bar in % to Q-max
- Error messages in display incl. logging

STANDARD SPECIFICATIONS

- Display full-color 5" touch display with 25 mm high digits digital
- Segments high resolution touch display
- Graduation 0,1, 0,2, 0,5, 1, 2, 5, 10, 20 or 50 kg (see specifications sheet of the weighing system)
- Housing polymer (ABS)
- Bracket RAM bracket
- Colour dark grey with red border
- Protection class IP65 / NEMA 4
- Power supply 12V (230V for stationary applications)
- Power consumption 160 mA (without options)
- Dimensions L x B x H = 85 x 165 x 115 mm (excl. bracket)



Management System
ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
www.tuv.com
ID 000037200

OPTIONS*

- Thermal or matrix printer
- WiFi and/or Bluetooth 2.0, RS232 option board for COM1 and COM2
- Ticket label printer
- Relay setpoint switch, for automatic dosing
- Analogue output -20 mA
- Legal for trade
- Multirange graduation (see specification sheet of the weighing system)
- RDC, RAVAS Data Collector Software
- RIS, RAVAS Integration Software

RAVAS Europe B.V.

Toepadweg 7, 5301 KA Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

