

# RAVAS Indicator 320

Weight indicator with extended scale functions

## BENEFITS

- Code entry, lb/kg toggle
- Relay for automatic dosing
- Display with backlight
- Internal clock for date/time
- For warehousing, dosing and mixing
- Connectivity for RAVAS Indicator App



Top quality  
Advanced functions



# RAVAS

# RAVAS Indicator 320

## FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare by push button
- Tare entry by cursor function
- Totaling with sequence number
- Code entry for max. 5-digit codes, by cursor function
- Three data output modes: print, continuous and command/answer
- lb or kg toggle
- Internal clock (for recording date/time on printout)
- Error messages in display
- Power supply to printer switched on and off by indicator
- Automatic shut-off function, defined by parameter setting
- Low battery indication
- Connectivity for RAVAS Indicator App

## STANDARD SPECIFICATIONS

- |                     |   |
|---------------------|---|
| ▪ Display           | digital   |
| ▪ Segments          | LCD, digit height 0.79 inch, backlight, dual color                      |
| ▪ Graduation        | 0.2, 0.5, 1, 2, 5, 10, 20 or 50 lb (see specifications weighing system) |
| ▪ Housing           | plastic (ABS)   |
| ▪ Bracket           | steel   |
| ▪ Colour            | red (RAL 3000)  |
| ▪ Protection class  | NEMA 4 / IP65   |
| ▪ Power supply      | 12V (230V for stationary applications)                                  |
| ▪ Power consumption | 35 mA   |
| ▪ Dimensions        | exc. bracket: 2.4 x 3 x 7.2 inch  |

## OPTIONS\*

- |  |                                      |
|--|--------------------------------------|
| ▪ Printer output to thermal or matrix printer                      | ▪ Explosion proof version (Exd)      |
| ▪ Data transfer to devices that have WiFi or Bluetooth® technology | ▪ RDC, RAVAS Data Collector Software |
| ▪ Relay setpoint switch, for automatic dosing                      | ▪ RIS, RAVAS Integration Software    |
| ▪ RS232 output for cable connection to truck terminal              |                                      |
| ▪ Multirange graduation (see specifications weighing system)       |                                      |

**RAVAS USA, INC.**  
1500 Enterprise Parkway  
Twinsburg, OH 44087  
T: +1 (330) 425 3092  
[www.ravasusa.com](http://www.ravasusa.com)

The RAVAS logo consists of the word "RAVAS" in a bold, black, sans-serif font. Above the letters "A" and "V" is a thick red horizontal bar.