

RAVAS Indicator Touch

Programmable 7.1 inch touch screen weight indicator

BENEFITS

- 7.1 inch high resolution touch screen
- Programmable user interface
- Intuitive, user friendly graphics
- USB port for data capture and transfer
- Advanced scale functions, e.g. dosing
- Wireless output optional
- Legal for Trade version OIML III optional



7.1 inch touch screen
Advanced weighing



RAVAS

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare via touch screen
- Entry of alphanumeric codes
- Totalling with sequence number
- Piece counting by sampling or entering of piece weight
- Internal clock
- Error messages in display
- Low battery indication
- Different basic functionality programs: weighing, counting (counting by sampling, counting by piece weight entry, counting based on database values, counting by combined tare values), registration of dosing data



STANDARD SPECIFICATIONS

- | | |
|---------------------|---|
| ▪ Display | OLED, digital touch screen |
| ▪ Graduation | 0.1, 0.2, 0.5, 1, 2, 5, 10, 20 or 50 kg
(see specifications weighing system) |
| ▪ Housing | stainless steel |
| ▪ Protection class | IP65 / NEMA 4 |
| ▪ Power supply | 12V (230V for stationary applications) |
| ▪ Power consumption | 300 mA |
| ▪ Dimensions | excl. cable glands: 225 x 190 x 45 mm |



Management
System
ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
www.tuv.com
ID 0000037200

OPTIONS*

- | | |
|--|-------------------------------------|
| ▪ Client specific software | ▪ Barcode scanner/printer |
| ▪ Wireless data transfer to devices that have WiFi or Bluetooth® technology | ▪ 0 to 20 mA output 32500 divisions |
| ▪ Legal for Trade version, OIML III | ▪ Relay output |
| ▪ Printer output to thermal or matrix printer | |
| ▪ Extra data output (RS232, RS485, 20 mA CL passive, 2 x 4-20 mA, 0-10V passive) | |

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

RAVAS