# RAVAS ProLine 2560 Exi / 2560 Exi INOX

Explosion proof pallet truck scale



# **BENEFITS**

- Superb accuracy
- Designed for hazardous environments
- Stainless steel fork cover
- RAVAS ProLine 2560 Exi INOX: Full stainless steel chassis
- For mixing and batching in Zone 1&21 or 2&22
- Rotating indicator, display visible from all sides
- System certification:
  ATEX II 2 G Ex ib IIC T4 Gb
  ATEX II 2 D Ex tb [ib] IIIC T60°C Db
- System certification with WiFi:
  ATEX II 2 G Ex ib IIB T4 Gb
  ATEX II 2 D Ex tb [ib] IIIC T60°C Db
- Rechargeable battery
- Large LCD display with backlight

The hi-tech standard Extremely accurate





Note: Image of RAVAS ProLine 2560 Exi INOX not shown in this document.



# **RAVAS ProLine 2560 Exi / 2560 Exi INOX**

# **FUNCTIONS**

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare by push button
- Automatic switch-of after 10/30/60 minutes of non-use
- Numeric keypad with large digits
- On/off key
- Internal clock
- kg/lb setting

# STANDARD SPECIFICATIONS

Weighing capacity 2,000 kgGraduation multirange

0 - 200 kg: graduation 0.1 kg 200 - 400 kg: graduation 0.2 kg 400 - 2,000 kg: graduation 0.5 kg

Max. tolerance
 0.08% of the load lifted

Display backlight LCD, digit height 25 mm

Protection class system IP65

indicator and battery IP66

terminal IP67

Battery 18Vdc/8Ah, NiMh battery pack

charger included

Battery life 60 hours / 40 hours (WiFi)

Charger 230V/18Vdc - 0,9 A
 Charging time approximately 6 hours
 Steering wheels rubber, antistatic
 Loading wheels polyurethane, tandem

Temperature operating at -10°C to 40°CColour red (RAL 3000), painted

Own weight 150 kg

System certification ATEX II 2 G Ex ib IIC T4 Gb


ATEX II 2 D Ex tb [ib] IIIC T60°C Db

ATEX II 2 D Ex tb [ib] IIIC T60°C Db

System certification ATEX II 2 G Ex ib IIB T4 Gb

with WiFl

# **DIMENSIONS IN MM**



Sta	nd	lar	'n
Jua	ΙIU	ıaı	u

Α	Fork length	1150
В	Fork width	160
С	Minimum fork height	90
D	Maximum fork height	200
	Lifting height	110
Ε	Width over forks	550
F	Height to top indicator	1270

# **WIFI OPTION**

The RAVAS ProLine 2560 Exi is available with a WiFi option. Please note that this option requires a specific chassis. The WiFi option must therefore be registered upon ordering and can not be retrofitted to a standard chassis.

# **INOX SPECIFICATIONS**

Color stainless steel

Steering wheels nylor

Loading wheels nylon, tandem

# nylon





System ISO 9001:2015 ISO 14001:2015 ISO 45001:2018 www.tuv.com ID 0000037200

#### **OPTIONS\***

- Legal for trade version, OIML III
- Extra NiMh battery pack
- WiFi output
- Stainless steel truck with galvanized pump
- Intrinsically safe analog output 4 20mA, not in combination with WiFi and can not be retrofitted
- Footbrake
- Different fork dimensions (fork height 90 mm)
- Different steering or loading wheels

#### **RAVAS Europe B.V.**

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands T: +31 418 515220 E: salesoffice@ravas.com WWW.RAVAS.COM

