RAVAS Indicator 110

Weight indicator with basic scale functions



BENEFITS

- Developed for mobile use
- Compact, robust and shock proof
- Integrated voltage converter
- Dust and watertight

Top quality
Connects to WMS





RAVAS Indicator 110

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare by push button
- Tare entry by cursor function
- Totalling with sequence number
- Error messages in display
- Power supply to printer switched on and off by indicator
- Automatic shut-off function, defined by parameter setting
- Low battery indication



STANDARD SPECIFICATIONS

Display digital

Segments
 LCD, digit height 0.7 inch

• Graduation 0.2, 0.5, 1, 2, 5, 10, 20 or 50 lb (see

specifications weighing system)

Housing plastic (ABS)

Bracket steel

Color red (RAL 3000)Protection class NEMA 4 / IP65

Power supplyPower consumption18 mA

Dimensions excl. bracket: 2.4 x 3 x 7.2 inch

OPTIONS*

- Thermal or matrix printer in separate housing
- Integrated power converter 24V-72V for indicator power supply via truck battery
- Multirange graduation (see specifications weighing system)

RAVAS USA, INC.

1500 Enterprise Parkway Twinsburg, OH 44087 T: +1 (330) 425 3092 www.ravasusa.com

