

RAVAS 2100 Zone 2&22

Explosion proof pallet truck scale



BENEFITS

- System certification
Zone 2: II 3 G Ex ic IIB T6 Gc IIB
Zone 22: II 3 D Ex ic IIIC T85°C Dc
- Rechargeable battery pack
- Stainless steel forks
- Antistatic steering wheel
- Intrinsically safe indicator board
- Rotating indicator (option)
- For mixing and batching in zone 2&22!

Top quality

For hazardous areas



RAVAS


FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare over the full scale. Pre-set tare maximum first range (200 kg)
- Error messages in display
- Automatic switch-off after 30 minutes of non-use
- Low battery warning in display

STANDARD SPECIFICATIONS

- Weighing capacity 2,000 kg
- Graduation multirange:
0 - 200 kg: graduation 0.2 kg
200 - 500 kg: graduation 0.5 kg
500 - 2.000 kg: graduation 1 kg
- Max. tolerance 0.1% of the load lifted
- System certification Zone 2: II 3 G Ex ic IIB T6 Gc IIB
Zone 22: II 3 D Ex ic IIIC T85° Dc
- Display LCD, digit height 18 mm
- Keypad foil keypad, 3 function keys, on/off key, resistant to chemicals
- Protection class load cells IP67, indicator IP65
- Fork shoes stainless steel
- Battery intrinsically safe, 12Vdc, rechargeable
- Battery life 100 hours, low battery indication
- Charger 230V/8Vdc - 1 A; for use outside hazardous zone
- Charging time approximately 8 hours
- Steering wheels rubber, antistatic
- Loading wheels polyurethane, tandem
- Colour red (RAL 3000), epoxy painted
- Own weight 145 kg
- Pump quick lift

DIMENSIONS IN MM



	Standard	Premium*
A Fork length	1150	950 - 2400
B Fork width	170	155
C Minimum fork height	90	86
Space underneath fork	22	
D Maximum fork height	180	176
Lifting height	90	
E Width over forks	555	450 - 900
F Height to top indicator	800	600

* Selected chassis for non-standard dimensions

For approved versions, class OIML III : European approval no. T2782, switch-of of display when tilting more than 2°. Graduation: multirange 0.5/1 kg, or one of the following fixed graduations:

- 1.000 divisions: 1.0/1,000 kg or 2.0/2,000 kg
- 2.000 divisions: 0.5/1,000 kg or 1.0/2,000 kg



Management System
ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
www.tuv.com
ID 0000037200

OPTIONS*

- Legal for trade version, OIML III
- Rotating indicator
- Footbrake

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

