

PRINTERS

6V thermal printer



Specifications:

- **Printer:** 6V, thermal (APS EPM203 mrs)
- **Power supply:** 6V, from 4 AA batteries inside indicator
- **Operating temperature:** 0 - 50 °C / 32 - 122 °F
- **Dimensions:** 3.0" x 3.0" x 1.7"
- **Print resolution:** 200 DPI
- **Print speed:** 3 lines / sec
- **Characters per line:** max. 48
- **Paper width:** 2.3"
- **Print width:** 1.9"
- **Paper roll diameter:** 1.3"

Suitable for light printing and weighing applications only



12V thermal



12V matrix



12V label

PRINTERS

12V thermal printer



Specifications:

- **Printer:** 12V, thermal (Martel MCP7810V)
- **Power supply:** 12V, hardwired from forklift battery
- **Operating temperature:** 0 - 50 °C / 32 - 122 °F
- **Dimensions:** 3.4" x 5.9" x 2.2"
- **Print resolution:** 200 DPI
- **Print speed:** max. 10 lines / sec
- **Characters per line:** max. 48
- **Paper width:** 2.3"
- **Print width:** 1.9"
- **Paper roll diameter:** 1.8"



6V thermal



12V matrix



12V label

PRINTERS

12V matrix printer



Specifications:

- **Printer:** 12V, matrix (Martel MCP6701)
- **Power supply:** 12V, hardwired from forklift battery
- **Operating temperature:** -5 - 50 °C / 23 - 122 °F
- **Dimensions:** 4.9" x 7.6" x 3.6"
- **Print resolution:** 77 DPI
- **Print speed:** 2.5 lines / sec
- **Characters per line:** 24
- **Paper width:** 2.2"
- **Print width:** 1.9"
- **Ink ribbon cartridge:** standard ERC-09



6V thermal



12V thermal



12V label