

RAVAS ProLine Touch GMP

Hygienic stainless steel hand pallet truck



BENEFITS

- Fully stainless steel chassis, electropolished for use in GMP environments
- Stainless steel chassis material class 316 AISI
- Minimal maintenance, easy cleaning and high resistance to corrosion
- Open under-fork construction, closed fork-shoe, for maximum hygiene
- Hydraulic equipment contains food grade oil
- Continuous weld: welds are polished
- Electro polishing, for very smooth surfaces

Hygienic

Made in Europe



RAVAS

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare via touch screen
- Entry of alphanumeric codes
- Totalling with sequence number
- Piece counting by sampling or entry of piece weights
- Error messages in display
- Internal clock
- USB port for data capture


STANDARD SPECIFICATIONS

- Weighing capacity 2,000 kg
- Graduation multirange:
 - 0 - 200 kg: graduation 0.1 kg
 - 200 - 400 kg: graduation 0.2 kg
 - 400 - 2.000 kg: graduation 0.5 kg
- Max. tolerance 0.08% of the load lifted
- Display 18 cm / 7.1 inch, high resolution touch screen
- Protection class load cells IP65, indicator IP65
- Battery 19,2V with 4 interchangeable battery modules 4,8V - 9Ah
- Battery life 16 hours, charging time 6 hours
- Charger NiMH charger (2 pieces)
- Steering wheels nylon
- Loading wheels nylon, tandem
- Pump ergonomic lift, stainless steel
- Own weight 170 kg

HYGIENIC CONSTRUCTION

- All bearings are made of stainless steel, are waterproof and self-lubricated
- Stainless steel housing, designed for GMP cleaning requirements
- Fork construction designed to allow effective cleaning and drainage, in accordance with GMP principles
- To prevent corrosion on the stainless steel parts, we recommend cleaning them monthly with Pelox cleaner

DIMENSIONS IN MM



	Standard Chassis	Stainless Steel
A Fork length	1150	1150
B Fork width	160	170
C Minimum fork height	90	90
Minimum clearance	22	
D Maximum fork height	205	202
Lifting height	115	
E Width over forks	550	540
F Height to top indicator	1185	1165



Management System
ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
www.tuv.com
ID 0000037200

OPTIONS*

- Client specific software
- 4 extra exchangeable batteries
- Legal for trade version, OIML III
- 0.1 kg graduation, maximum 1,000 kg capacity
- RS232 output
- Thermal / matrix printer
- SOLAS version

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

