

RAVAS Indicator 2100

Weight indicator with basic scale functions

BENEFITS

- Developed for mobile use
- Compact, robust and shock proof
- Data transfer to devices that have Bluetooth® technology
- Integrated voltage converter
- Dust and watertight



Top quality
Connects to WMS



RAVAS

RAVAS Indicator 2100

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare
- Tare entry by cursor function
- Totaling with sequence number
- Error messages in display
- Printer power supply via indicator
- Automatic shut-off function defined by parameter settings
- Low battery indication

STANDARD SPECIFICATIONS

- | | |
|---------------------|---|
| ▪ Display: | digital |
| ▪ Segments: | LCD, digit height 18 mm |
| ▪ Graduation: | 0.1, 0.2, 0.5, 1, 2, 5, 10, 20 or 50 kg (see specifications of weighing system) |
| ▪ Housing: | plastic (ABS) |
| ▪ Bracket: | steel |
| ▪ Colour: | red (RAL 3000) |
| ▪ Protection class: | IP65 / NEMA 4 |
| ▪ Power supply: | 12V (230V for stationary applications) |
| ▪ Dimensions: | excl. bracket: 60 x 77 x 182 mm |

OPTIONAL*

- Printer output to thermal or matrix printer
- Wireless data transfer to devices that have WiFi or Bluetooth® technology
- RS232 output for cable connection to truck terminal
- Multirange graduation (see specifications weighing system)
- Explosion proof version (Exi)

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

